



## 612 Style Time Zone Clock



Model 612A - 2.5" time & 1.8" date or 4.0" time & 2.5" date,  
1.0" & 1.5" zone labels, 5 zones

The 612 series time zone clocks have user changeable multi-color bar-segment LED time and date with white vinyl zone labels for each zone. 612 models displays 5 time zones.

Each 612 clock comes standard with an OCXO oscillator, which is accurate to .06 seconds per year.

For easy clock management, an infrared (IR) remote control is included with every 612 model. An optional BRG Time Commander IR Touch Pad Remote control to use with all of your time zone clocks.

### Features:

- OCXO oscillator accurate to .06 seconds per year
- 1.8", 2.5" or 4.0" user changeable multi-color bar segment LEDs for displaying time & date (red, blue, green, yellow, magenta, cyan & white LED colors)
- 1.0" or 1.5" white vinyl lettering for displaying zone names
- Model displays 5 separate time zones
- 12 or 24 hour format
- DST and time zone offsets supported
- IR remote control included
- Black brushed Aluminum frame
- Multiple cord lengths available
- US, British, Australian or European plugs
- 100-240 VAC. 50-60 cycle power
- Available on GSA, contract GS-02F-0030U



### Oven Controlled Crystal Oscillator (OCXO)

- Accurate to 2 PPB (parts per Billion) or .06 seconds per year or about 1 second in 20 years.
- 1 thousand times more accurate than most competing clocks
- Eliminates the need for GPS or Network time synchronization for

# 612 Style Time Zone Clock



Model	Zones	Displays		White Vinyl Label	Viewing Distance	Dimensions		
		Perimeter	Center			H	W	D
612A	5	2.5" Time / 1.8" Date	4.0" Time / 2.5" Date	1.0" / 1.5"	40-100 ft.	26.25	39.25	3.25

## Color Options



Red

Blue

Green

Yellow

Magenta

Cyan

White



Email: [sales@brgproducts.com](mailto:sales@brgproducts.com)  
Web Site: <http://www.brgproducts.com>

Copyright 2023, BRG Precision Products, All rights reserved. Printed in the USA, 612 Spec Sheet Rev 2.1.10.30.2023



600 N River Street • Derby, Kansas 67037  
800-295-0220 • 316-788-2000  
Fax: 316-788-7080